

GRANT OF EQUIPMENT
AUTHORIZATION
Certification
Issued Under the Authority of the
Federal Communications Commission
By:

Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204

Date of Grant: 07/21/2016
Application Dated: 07/20/2016

JDTECK INC
215 Celebration Place
Suite 190
Kissimmee, FL 34747

Attention: Dennison Jurawan , Sales Manager

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: SQX-DR-LCPA-27
Name of Grantee: JDTECK INC
Equipment Class: Part 20 Industrial Booster (CMRS)
Notes: Broadband Booster

Grant Notes

FCC Rule Parts	Frequency Range (MHZ)	Output Watts	Frequency Tolerance	Emission Designator
27	698.0 - 719.0	0.204		F9W
27	698.0 - 719.0	0.204		G7D
27	698.0 - 719.0	0.204		G7W
27	698.0 - 719.0	0.204		G7W
27	728.0 - 746.0	0.275		F9W
27	728.0 - 746.0	0.275		G7D
27	728.0 - 746.0	0.275		G7W
27	728.0 - 746.0	0.275		G7W
27	776.0 - 787.0	0.234		F9W
27	776.0 - 787.0	0.234		G7D
27	776.0 - 787.0	0.234		G7W
27	776.0 - 787.0	0.234		G7W
27	746.0 - 757.0	0.316		F9W
27	746.0 - 757.0	0.316		G7D
27	746.0 - 757.0	0.316		G7W
27	746.0 - 757.0	0.316		G7W
22H	824.0 - 849.0	0.057		F9W
22H	824.0 - 849.0	0.057		G7D
22H	824.0 - 849.0	0.057		G7W
22H	824.0 - 849.0	0.057		G7W
22H	869.0 - 894.0	0.269		F9W
22H	869.0 - 894.0	0.269		G7D
22H	869.0 - 894.0	0.269		G7W
22H	869.0 - 894.0	0.269		G7W
24E	1850.0 - 1915.0	0.117		F9W
24E	1850.0 - 1915.0	0.117		G7D
24E	1850.0 - 1915.0	0.117		G7W
24E	1850.0 - 1915.0	0.117		G7W
24E	1930.0 - 1995.0	0.66		F9W
24E	1930.0 - 1995.0	0.66		G7D
24E	1930.0 - 1995.0	0.66		G7W
24E	1930.0 - 1995.0	0.66		G7W
27	1710.0 - 1755.0	0.12		F9W
27	1710.0 - 1755.0	0.12		G7D
27	1710.0 - 1755.0	0.12		G7W
27	1710.0 - 1755.0	0.12		G7W
27	2110.0 - 2155.0	0.66		F9W
27	2110.0 - 2155.0	0.66		G7D
27	2110.0 - 2155.0	0.66		G7W
27	2110.0 - 2155.0	0.66		G7W

Power output listed is conducted. The antenna(s) used for this transmitting device must be professionally installed to provide a separation distance of at least 103cm from all persons. Installers and end-users must be provided with antenna installation instructions and transmitting device operating conditions for satisfying RF exposure compliance.

The installation height of the antenna for AWS band (1700/2100 MHz) operations is limited to 10 meters above ground for compliance with 47 CFR 27.50