

**TCB**

**GRANT OF EQUIPMENT  
AUTHORIZATION**

**TCB**

**Certification  
Issued Under the Authority of the  
Federal Communications Commission**

**By:**

**Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204**

**Date of Grant: 07/20/2016**

**Application Dated: 07/20/2016**

**JDTECK INC  
215 Celebration Place  
Suite 190  
Kissimmee, FL 34747**

**Attention: Dennison Jurawan , Sales Manager**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE,  
and is VALID ONLY for the equipment identified hereon for use under the  
Commission's Rules and Regulations listed below.

**FCC IDENTIFIER: SQX-DR-LCPA-37**

**Name of Grantee: JDTECK INC**

**Equipment Class: Part 20 Industrial Booster (CMRS)**

**Notes: Multi-Band Industrial Digital Repeater**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	27	698.0 - 716.0	0.107		F9W
	27	698.0 - 716.0	0.107		G7D
	27	698.0 - 716.0	0.107		G7W
	27	698.0 - 716.0	0.107		GXW
	27	728.0 - 746.0	2.512		F9W
	27	728.0 - 746.0	2.512		G7D
	27	728.0 - 746.0	2.512		G7W
	27	728.0 - 746.0	2.512		GXW
	27	776.0 - 787.0	0.105		F9W
	27	776.0 - 787.0	0.105		G7D
	27	776.0 - 787.0	0.105		G7W
	27	776.0 - 787.0	0.105		GXW
	27	746.0 - 757.0	2.818		F9W
	27	746.0 - 757.0	2.818		G7D
	27	746.0 - 757.0	2.818		G7W
	27	746.0 - 757.0	2.818		GXW
	22H	824.0 - 849.0	0.105		F9W

<b>22H</b>	<b>824.0 - 849.0</b>	<b>0.105</b>	<b>G7D</b>
<b>22H</b>	<b>824.0 - 849.0</b>	<b>0.105</b>	<b>G7W</b>
<b>22H</b>	<b>824.0 - 849.0</b>	<b>0.105</b>	<b>GXW</b>
<b>22H</b>	<b>869.0 - 894.0</b>	<b>2.57</b>	<b>F9W</b>
<b>22H</b>	<b>869.0 - 894.0</b>	<b>2.57</b>	<b>G7D</b>
<b>22H</b>	<b>869.0 - 894.0</b>	<b>2.57</b>	<b>G7W</b>
<b>22H</b>	<b>869.0 - 894.0</b>	<b>2.57</b>	<b>GXW</b>
<b>24D</b>	<b>1850.0 - 1915.0</b>	<b>0.234</b>	<b>F9W</b>
<b>24D</b>	<b>1850.0 - 1915.0</b>	<b>0.234</b>	<b>G7D</b>
<b>24D</b>	<b>1850.0 - 1915.0</b>	<b>0.234</b>	<b>G7W</b>
<b>24D</b>	<b>1850.0 - 1915.0</b>	<b>0.234</b>	<b>GXW</b>
<b>24D</b>	<b>1930.0 - 1995.0</b>	<b>4.897</b>	<b>F9W</b>
<b>24D</b>	<b>1930.0 - 1995.0</b>	<b>4.897</b>	<b>G7D</b>
<b>24D</b>	<b>1930.0 - 1995.0</b>	<b>4.897</b>	<b>G7W</b>
<b>24D</b>	<b>1930.0 - 1995.0</b>	<b>4.897</b>	<b>GXW</b>
<b>27</b>	<b>1710.0 - 1755.0</b>	<b>0.148</b>	<b>F9W</b>
<b>27</b>	<b>1710.0 - 1755.0</b>	<b>0.148</b>	<b>G7D</b>
<b>27</b>	<b>1710.0 - 1755.0</b>	<b>0.148</b>	<b>G7W</b>
<b>27</b>	<b>1710.0 - 1755.0</b>	<b>0.148</b>	<b>GXW</b>
<b>27</b>	<b>2110.0 - 2155.0</b>	<b>4.841</b>	<b>F9W</b>
<b>27</b>	<b>2110.0 - 2155.0</b>	<b>4.841</b>	<b>G7D</b>
<b>27</b>	<b>2110.0 - 2155.0</b>	<b>4.841</b>	<b>G7W</b>
<b>27</b>	<b>2110.0 - 2155.0</b>	<b>4.841</b>	<b>GXW</b>

Booster. Power output listed is conducted. The antenna(s) used for this transmitting device must be professionally installed to provide a separation distance of at least 304 cm from all persons. Installers and end-users must be provided with antenna installation instructions and transmitting device operating conditions for satisfying RF exposure compliance

The installation height of the antenna for AWS band (1700/2100 MHz) operations is limited to 10 meters above ground for compliance with 47 CFR 27.50