

**SPECIFICATIONS**

Description	Specification
Frequency Range	698-960 / 1710-2700 MHz
Gain	3 dBi
VSWR	< 1.5:1 avg
Impedance	50 $\Omega$
Polarization	Linear, Vertical
BW/Azimuth	360 °
BW/Elevation	110 °
Max Power Input	50W
Connector	N (Female)
Dimensions	100 x 130 mm (3.9" x 5.1")
Weight	0.526 lb / (239g)
Temperature	-40°C ~ +80°C
Mounting	Pole / Wall
Color	Ivory

**Application Image**



Low Profile



N Female Connector



Mounting Bracket

**FEATURES:**

This Omni Directional Antenna is ideal for applications where multiple service providers need to be supported or line of sight (LOS) to the nearest cell tower is not available. Supports a wide range of protocols, these include; WLL, GPS, WLAN, WISP, WiMax, SCADAA, LMR, Cellular, Paging, PCS, LTE and AWS applications The mounting brackets included allow this antenna to be installed either on a flat surface or antenna mast / pole. All JDTECK's antennas are tested for optimal return loss before shipping.

- Multi-Band (698-2700 MHz)
- Low Profile 3.9" x 5.1"
- High Quality UV Protected Enclosure
- Good return loss values.